



Pressure: 20 bar fluid  
 Test pressure: 30 bar  
 max. Temperatur: 110 °C  
 Inlet/Outlet: 5/4" BSPF  
 Surface treatment inside: pickled  
 Surface treatment outside: mechanical polished or glass pearl blasted

Sealing: see PO documents  
 Vent: 1/4" BSPF  
 Pressure Equipment Directive: 97/23/EC: Article 3/Clause 3

quant.	description	item/no.	size	material	drawing id./standard	kg/part
1	O-Ring	15	Ø95x2,5	EPDM/Viton		
3	Leg	14		SUS304		
1	Outlet	13	1 1/4 BSP Female	SUS304		
1	Basket	12	Ø95x340	SUS304		
1	Inlet	11	1 1/4" BSP Female	SUS304		
1	O-ring	10	Ø118x6	EPDM/Viton		
1	Top Cover	9		SUS304		
1	Gauge Port	8	1/4" BSP Female	SUS304		
3	Bolt&Nut	7	M12	SUS304		
1	Bottom Flange	6		SUS304		
1	Spring	5	Ø105xØ4x180	SUS304		
1	Clamp	4		SUS304		
2	Bolt	3		SUS304		
1	Body	2	Ø114x2	SUS304		
1	Bottom Cover	1	Ø114x2	SUS304		

DATE	NAME	CUSTOMER:	 A-4860 LENZING - AUSTRIA
DESIG.	-	PROJECT:	
CHECK			
APPR.			
SCALE	DESCRIPTION: Bagfilterhousing Type: LT-BFBC-1-4		POS./PIECE TO DWG. ID
			DRAWING ID / REVISION
			IN EXCHANGE FOR / REPLACED BY
			DRAWING ID / REVISION
			PIECE LIST NO. PAGE NO.
			DRAWING ID / REVISION
WE RESERVE THE COPYRIGHT TO THIS TECHNICAL DRAWING. NO COPYING, MAKING ACCESSIBLE OR PASSING ON TO THIRD PARTIES, PARTICULARLY COMPETITORS, WITHOUT OUR EXPRESS CONSENT (§ 1, NO. 3 OF THE LAW OF JUNE 19th 1901).			ADDITIONAL CLASSIFICATION F PLANT CLASSIFICATION DRAWING ID REV.