



## Expansion joint variants

	Elastomer expansion joint	Multilayer expansion joint
<b>Temperature:</b>	up to 200 °C	up to 400 °C
<b>Design:</b>	Single-layer elastomer expansion joint fully joined with one or more fabric reinforcement inserts	Multilayer fabric expansion joint consisting of interior insulating layers, embedded sealing films and exterior pressure carrier fabrics
<b>Material:</b>	<p><b>Rubber grades:</b>                      up to 100 °C: EPDM, IIR, CSM, NBR                      up to 180 °C: FPM                      up to 200 °C: Silicon (Q)</p> <p><b>PTFE lining:</b>                      Permanently embedded on the inside at the rubber bellows in order to withstand corrosive chemical attack, available starting at NB 300</p> <p><b>Inserts:</b>                      Nylon, polyester, Kevlar, glass fibre, and steel mesh</p>	<p><b>Internal layers:</b>                      PTFE glass fibre fabric laminate, glass fibre fabric, glass mat, silicate fabric</p> <p><b>Sealing films:</b>                      PTFE film, stainless steel film</p> <p><b>External layer:</b>                      Silicon coated glass fibre fabric                      PTFE-glass fibre fabric laminate</p>

## Flanges

<b>Design:</b>	Single-part or multi-part backing flanges with clearance holes
<b>Flange norms:</b>	According to customer specification
<b>Materials:</b>	Carbon steel: 1.0038 (S235JRG2) Stainless steel: 1.4301 (X5CrNi18-10) 1.4571 (X6CrNiMoTi17-12-2) Other materials on request
<b>Coating:</b>	Primed, hot-dip galvanised, special paint

## Flow liners

<b>Design:</b>	Cylindrical, conical or telescoping flow liner (▶ page 296)	
<b>Materials:</b>	Carbon steel: 1.0038 (S235JRG2) 1.0570 (S355J2G3) 1.0425 (P265GH) 1.5415 (16Mo3) 1.4713 (X10CrAl7)	Stainless steel: 1.4301 (X5CrNi18-10) 1.4571 (X6CrNiMoTi17-12-2) 1.4828 (X15CrNiSi20-12) Other materials on request
<b>Coating:</b>	Primed, hot-dip galvanised, special paint	

## Optional accessories

<b>Fixing:</b>	Screws Nuts Washers Disc springs
----------------	---

